

Vapour Control Layer

Product Description

Vapour Control Layer is a traditional specification, single-ply, non-laminated, virgin grade blown polythene material. It is designed for use as an air leakage barrier and vapour control layer (AVCL) in insulated wall, roof and floor applications. Vapour Control Layer must be installed in conjunction with our two-tape sealing system to provide a fully airtight seal.



Features

- Air-leakage barrier and vapour control layer (AVCL)
- Supplied multi-folded in 4m x 25m
- Virgin grade high quality material
- CE Approved and CPR compliant
- Complies with BS EN 13984
- Easy to install, can see battens (translucent green tint)
- Minimises interstitial condensation
- Improves the insulation performance
- Low cost solution
- Helps buildings to meet BS 5250:2011

Roll Detail	
Standard Width (M-fold)	4m
Roll Weight	27kg
Roll Length	25m
Packing	50 Rolls per pallet
Total thickness	300/1200 Micron/Gauge

Please note: The above technical information is given as a guide and is based on recent test data obtained under laboratory conditions. Materials should be fully tested by the end user to establish suitability of the product for the intended application. October 2014

Premier Sealant Systems Ltd

Mercia Way Foxhills Industrial Park Scunthorpe, DN15 8RE, England

Tel. 01724 864100 | Fax. 01724 860116 | Email. sales@premiseal.co.uk | Website. www.premiseal.co.uk